

CLAIMS

a second means (6, 18; 101, 129) for discharging the joined components during simultaneous deformation of a layer structure, obtained in the joining, to provide a homogeneous mixture of components,

15 a receiving means (15; 115) rotatable about a longitudinal axis (13; 113) and having a receiving surface (22; 122) facing the layering means (8; 108) and arranged radially outwardly of the same,

the receiving means (15; 115), while rotating, being adapted to support said stratum.

3. A device as claimed in claim 2, c h a r a c -
t e r i s e d in that the layering means (8; 108) is
rotatable in a direction of rotation (P_1 ; P_{101}) which is
opposite to the direction of rotation (P_2 ; P_{102}) in which
the receiving means (15; 115) is rotatable.

4. A device as claimed in claim 2 or 3, characterised in that layering means (8; 108) is rotatable with a first angular velocity (ω_1 ; ω_{101}), and the receiving means (15; 115) is rotatable with a second

angular velocity (ω_2 ; ω_{102}) differing from the first angular velocity (ω_1 ; ω_{101}).

5. A device as claimed in claim 4, characterised in that the first angular velocity (ω_1 ; ω_{101}) is in the range 30-85 rad/s.

6. A device as claimed in claim 4 or 5, characterised in that the second angular velocity (ω_2 ; ω_{102}) is in the range 30-85 rad/s.

7. A device as claimed in any one of the preceding claims, characterised in that the layering means comprises a nozzle for each of the components, each nozzle being adapted to dispose thin layers of the component supplied thereto on the receiving surface (22; 122).

8. A device as claimed in any one of claims 2-6, characterised in that the layering means (8; 108) comprises a blade means (10; 110) which is rotatable about said longitudinal axis (13; 113) and which during rotation is adapted to engage with the components supplied thereto and subsequently throw them away to dispose thin layers of the components on the receiving surface (22; 122).

9. A device as claimed in any one of the preceding claims, characterised in that the receiving means (15) is adapted to transfer the stratum to the second means (6, 18).

10. A device as claimed in claim 9, characterised in that the receiving means (15) comprises a body (17) having a conical interior circumferential surface (22) arranged concentrically about the longitudinal axis (13) and thus enclosing the layering means (8) and forming said receiving surface (22), the receiving means (15), during rotation and under the action of centrifugal forces, being adapted to convey said stratum towards the wider end (11) of the conical receiving surface (22), at which end (11) the stratum will be transferred to the second means (6, 18) in consequence of the rotation of the receiving means (15).

8/12/15
11. A device as claimed in claim 10, characterised in that the second means (6, 18) comprises a helical duct (6) which encloses the receiving means (15) and has a side open towards the receiving means (15), whereby the stratum continuously transferred from the receiving means (15) will be collected by said duct (6).

12. A device as claimed in claim 11, characterised in that the second means (6, 18) comprises in unison with the receiving means (15) rotatable discharge means (18), and that the duct (16) comprises an outlet connected thereto, the discharge means (18) being adapted to convey to the outlet (7) the stratum transferred to the duct (6) during deformation of its layer structure.

13. A device as claimed in claim 12, characterised in that each discharge means (18) comprises a vane (18) which is attached to the receiving means (15) and displaceable in the duct (6) and which during rotation of the receiving means (15) engages with the stratum transferred to the duct (6) and conveys it during simultaneous creasing thereof towards the outlet (7).

14. A device as claimed in any one of claims 1-8, characterised in that the second means (101, 129) comprises a scraper element (129) for scraping off the stratum from the receiving surface (122), and that the receiving means (115) is adapted to transfer, during rotation thereof, the thus scraped-off stratum to a discharge unit (101) of the second means (101, 129).

15. A device as claimed in claim 14, characterised in that the receiving means (115) comprises a body (117) having a cylindrical interior circumferential surface (122) which is concentrically arranged about the longitudinal axis (113) and which thus encloses the layering means (108) and forms said receiving surface (122), and that the scraper element (129) is arranged along the receiving surface (122) for scraping off the

~~Sub B1~~

17. A method for mixing at least two components,
20 comprising the steps of
 joining the components in layers, and
 subsequently conveying the thus-joined components
in such manner that a layer structure obtained in connec-
tion with the joining is deformed to form a homogeneous
25 mixture of components,

alternately disposing, with the aid of a layering means (8; 108), thin layers of the components on a receiving means (15; 115) radially enclosing the layering means (8; 108) to form a stratum of layer structure, and by rotation of the receiving means (15; 115) supporting the stratum,

35 the layers in the circumferential direction being
distributed uniformly on the receiving means (15; 115)
in consequence of its rotation.

